



INSPIRED BY **DESIGN.**



T003M Arches

Manufacturing Specifications

Fiber Content:	Antron® Lumena™ Type 6,6 nylon
Dye Method:	Solution Dyed
Construction:	Interloop Patterned Loop
Carpet Tile Size:	12"W x 36"L
Tufted Fiber Weight:	24 oz.
Gauge:	1/12
Pile Height:	.219"

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	Limited 10-year Wear Warranty.

Arches meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP5300

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.