



9602 Bombay Vibration

Manufacturing Specifications

Fiber Content:	100% Invista Solution Dyed BCF Nylon Type 6,6
Dye Method:	Solution Dyed
Construction:	Loop
Pattern Repeat:	12" W x 11" L
Tufted Fiber Weight:	37 oz.
Gauge:	1/12
Pile Height:	.125"/.25"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year wear warranty.

Bombay Vibration meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

9602 Bombay Vibration

Color Line

00227 Flutter
00322 Cadence
00326 Undulate
00423 Surge
00530 Flare
00628 Twinkle
00629 Gleam
00720 Undertone
00724 Ripple
00725 Pulse
00821 Aura