



INSPIRED BY **DESIGN.**



9673 Himalayas

Manufacturing Specifications

Fiber Content:	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resistance
Dye Method:	Solution Dyed
Construction:	Tip Sheared Loop Pattern
Pattern Repeat:	24"W x 15.7"L
Tufted Fiber Weight:	36 oz.
Gauge:	1/12
Pile Height:	.375" / .250" / .125"

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	Limited 10-year Wear Warranty.

Himalayas meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.