



## 9567 Jive

### Manufacturing Specifications

Fiber Content:	100% Masland Solution Dyed BCF Nylon Type 6,6
Dye Method:	Solution Dyed
Construction:	Cut/Loop
Pattern Repeat:	18" W x 32" L
Tufted Fiber Weight:	34 oz.
Gauge:	1/10
Pile Height:	.093"/.218"/.375"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

### PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM <sup>2</sup> Class 1.  Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year wear warranty.

Jive meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

**9567 Jive**  
**Color Line**

00145 Rueda  
00463 Grand Plie'  
00544 Chasse  
00575 Aerial  
00655 Jazz Hands  
00696 Pirouette  
00763 Arabesque  
00847 Box Step  
00877 Promenade  
00898 Entrada