



9622 Karma

Manufacturing Specifications

Fiber Content:	100% Invista Solution Dyed BCF Nylon Type 6,6
Dye Method:	Solution Dyed
Construction:	Loop
Pattern Repeat:	36" W x 26" L
Tufted Fiber Weight:	44oz.
Gauge:	1/10
Pile Height:	.25"/.375"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year wear warranty.

Karma meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

9622 Karma

Color Line

00128 Awareness
00250 Breath
00347 Peaceful
00576 Compassion
00696 Brainwave
00742 Meditation
00779 Transformation
00782 Mindfulness
00797 Sensory
00831 Calm
00858 Visualize
00897 Immanence