



INSPIRED BY **DESIGN.**



T9995 Mateo

Manufacturing Specifications

Fiber Content:	100% Universal Fibers® Type 6 nylon
Dye Method:	Solution Dyed
Construction:	Pattern Loop
Pattern Repeat:	N/A
Tufted Fiber Weight:	12 oz.
Gauge:	1/12
Pile Height:	.250" / .125"

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	Limited 10-year Wear Warranty.

Mateo meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1922

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

Mateo
Color Line

601	Rain Forest
602	Breeze
603	Tropical
604	Paradise
605	Hazy Day
606	Slumber