



9560 Ursa

Manufacturing Specifications

Fiber Content:	100% Masland Approved BCF Nylon Type 6,6
Dye Method:	Continuous
Construction:	Pattern Loop
Pattern Repeat:	18" W x 28" L
Tufted Fiber Weight:	32 oz.
Gauge:	1/10
Pile Height:	.093"/250"/.343"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year wear warranty.

Ursa meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

9560 Ursa

Color Line

00128 Andromeda
00145 Lunar
00335 Celestial
00463 Star
00544 Supernova
00566 Planet
00579 Terrestrial
00587 Universe
00637 Millenium
00665 Galaxy
00693 Outer Space
00763 Astronomic
00773 Solar System
00793 Asteroid
00797 Black Hole
00838 Meteor
00877 Constellation
00898 Comet