



9601 Vivacity Manufacturing Specifications

Fiber Content:	100% Masland Approved BCF Nylon Type 6,6
Dye Method:	Continuous
Construction:	Loop
Pattern Repeat:	12" W x 12" L
Tufted Fiber Weight:	32 oz.
Gauge:	1/10
Pile Height:	.125"/.312"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene

PERFORMANCE SPECIFICATIONS

Flammability:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts/CM ² Class 1. Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density:	Passes NBS Smoke Chamber Test-ASTM E-662.
Colorfastness:	4.0 or better.
Static Rating:	Less than 3.5 kV.
Warranty:	10 year wear warranty.

Vivacity meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Green Label Plus Certification #GLP1678

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of federal law.

9601 Vivacity
Color Line

00132 Sparkle
00210 Ardor
00313 Spirit
00358 Vitality
00515 Zest
00516 Zeal
00617 Passion
00618 Pizzazz
00711 Verve
00797 Power
00814 Mojo
00912 Vigor